



# Shandong Shenjie Bearing Co., Ltd.



6.693 Inch | 170 Millimeter x 10.236 Inch | 260 Millimeter x 1.654 Inch | 42 Millimeter SKF NU 1034 M/C3 Cylindrical Roller Bearings

Bearing No. NU 1034 M/C3

NU 1034 M/C3 Bearing 2D drawings and 3D CAD models

Category	Cylindrical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	8.369
EAN	7316577012975
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	Plain Inner Ring   2 Rib Outer Ring   Cage on Outer Ring ID
Long Description	170MM Bore; Straight Bore Profile; 260MM Outside Diameter; 42MM Width;



## Shandong Shenjie Bearing Co., Ltd.

	Brass Cage Material; RBEC 1   ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C3-Loose Inte
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	NU 1034 M/C3
Weight / LBS	18.435
d	6.693 Inch   170 Millimeter
D	10.236 Inch   260 Millimeter
B	1.654 Inch   42 Millimeter
bore diameter:	170 mm
static load capacity:	400 kN
outside diameter:	260 mm
precision rating:	Not Rated
overall width:	42 mm
maximum rpm:	4300 RPM
flanges:	(2) Outer Ring
cage material:	Brass
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C3
outer ring width:	42 mm
ring separation:	Separable Ring
fillet radius:	2 mm
operating temperature range:	Maximum of +300 ° F



## Shandong Shenjie Bearing Co., Ltd.

series:	NU10
dynamic load capacity:	275 kN